625V

Displacement	Max power	Kerb weight	Seat height	Price*
578	**52** BHP 38.5 kW @ 8,500 rpm	**205** kg Curb weight	**700** mm	—

ENGINE & TRANSMISSION

Type	V-twin cylinder, 4-stroke, DOHC, 8 valves
Cooling system	Liquid-cooled / Zoned cooling
Max torque	52 N·m @ 6,000 rpm
Gearbox	6 Speed

CHASSIS & DIMENSIONS

Frame	Hybrid tubular / sheet metal cradle frame
Front suspension	Upside down damping unadjustabl
Front travel	130 mm
Rear suspension	Normal rear shock absorber
Rear travel	81 mm
Front brake	Single floating disc + opposed 4-piston caliper (TAISKO) / ABS
Rear brake	Fixed disc+opposed 2-piston calliper
Front tyre	120/70R18 (CST S level)
Rear tyre	160/60R16 (CST S level)
Fuel tank capacity	20 L (Main & Auxiliary dual-tank system)
Length × width × height L × W × H	2220 mm × 800 mm × 1115 mm

Emission standard Euro 5

SCAN ME

* Recommended retail price. On-the-road (OTR) charges are additional.
Specifications, equipment and colours are subject to change without prior notice. Please confirm all details with your dealer.